



FLEET
MANAGEMENT
SIMPLIFIED

LINK 240

MANAGE YOUR FLEET THE SIMPLEST WAY

LINK 240 is an entry-level vehicle tracking device for cars and light commercial vehicles. Just plug it into the vehicle's standard OBD-II connector and you're ready to go. It keeps you connected with your fleet and helps you identify where you can cut costs.

BENEFITS



STAY CONNECTED WITH YOUR FLEET

- Always know where your vehicles are and where your drivers have been.
- Simple self-installation by plugging your LINK 240 into the vehicle's OBD-II port.
- Take advantage of stronger data coverage with support for LTE-M and GPRS technology.¹



MAKE DRIVERS MORE EFFICIENT

- Improve your drivers' performance and safety with driving style analyses.



REDUCE YOUR COSTS

- Reduce running costs by monitoring fuel consumption and driving styles.
- Minimise vehicle downtime with vehicle malfunction instant alert and maintenance notifications.



CONTROL YOUR FLEET & BUSINESS

- Get notified when a vehicle is used without your permission.
- Manage your tax responsibilities more easily using automatic logbook.
- Identify areas where improvements can be made using comprehensive reports.

FEATURES



TRACK & TRACE

View the driving times, locations and mileage of your fleet in real time or over a chosen time period.



INSTANT ALERTS & CRASH DETECTION

Get notified whenever a vehicle enters or leaves a designated area and when an accident occurs.



REPORTING ON FLEET PERFORMANCE

Get 24/7 access to comprehensive vehicle and driver insight reports, e.g. trip and fuel consumption reports.

FLEET MANAGEMENT SIMPLIFIED

FEATURES



MILEAGE OVERVIEW & LOGBOOK FUNCTIONALITY

Mileage and trip data can be analysed either per group or for your entire fleet across a chosen time period. Logbook sorts private and business trip data, for a clear view of vehicle usage.



MONITOR FLEET HEALTH STATUS

LINK 240 reports instant vehicle diagnostic system incidents like MIL notifications and DTCs.²



DRIVING BEHAVIOUR

OptiDrive 360 provides driving style insights using up to eight performance indicators.²



FUEL CONSUMPTION

Read real-time and historical insights on your fleet's fuel usage.



POWER DISCONNECTED EVENTS

Get notified immediately when the LINK 240 is disconnected from the OBD-II port.



BATTERY POWERED OPERATION

Internal battery design provides minimum traceability of LINK 240 when it is disconnected from the OBD-II port and in standby mode.



OBD-II connector



2 x LEDs for system and connection status

SPECIFICATIONS

Dimensions: 57 x 48 x 27 mm

Weight: 55 g

Supply voltage: 12 V / 24 V
(min 9 V to max 30 V)

Temperature operation:
-20°C to +50°C

Protection class: IP20

Mobile networks: Integrated mobile network module with LTE-M and GPRS technology. Micro SIM only accessible with opened housing

GNSS: Integrated GNSS antenna and GNSS receiver

Rechargeable battery: As battery a Li-Ion battery with 250mAh is used for operational use

Current / power consumption:

At 14 V:

Typically: < 70 mA / < 1 W

During data transmission:
< 170 mA / < 2.4 W

At 28 V:

Typically < 40 mA / < 1.1 W,

During data transmission
< 110 mA / < 3.1 W

Standby: < 2 mA / < 0.03 W

¹ Depends on the availability of the local network infrastructure.

² MIL notifications DTCs and OptiDrive 360 KPIs all available subject to vehicle/model, and only accessible with WEBFLEET (not WEBFLEET LITE) subscription.

MIL: Malfunction Indicator Lamp; DTCs: Diagnostic Trouble Codes; OptiDrive 360 KPIs: speeding, constant speed, driving events, coasting, idling, green speed, fuel consumption and gear shifting.